



## SPECIFICATIONS

### MATERIAL

The B-1, 8" bollard shall be fabricated with 8" .188 wall pipe (8.625"OD), 2 ea. 3 inch and 1 ea. 4 inch decorative collars (9.625"OD) a sch. 40 weld cap and a 5/8" x 13-1/2" steel flange all fully welded. Steel shall conform to ASTM A53.

### PROTECTIVE COATINGS

**Powder Coating:** Following fabrication bollards shall be cleaned and treated with an iron phosphate process prior to the coating application. This process shall include a non-chromated alkaline cleaner, and an iron phosphate treatment followed with an acidic sealer for maximum adhesion. The protective coatings shall be either polyester or polyester TGIC powder. Following application the parts shall be baked until properly cured. The coating shall be a minimum of 4 mils thick on all surfaces.

**Note:** Unless otherwise specified, bollards shall be powder coated a standard FairWeather color.

**Options:** Sch 40 or sch 80 pipe, eye bolts

**Please Note:** Anchor Bolts By Others.

REV 4-20-06

# Model B-1, 8" Bollard with Surface Mount Option

## FairWeather Site Furnishings

360-895-2626 or Toll Free 800-323-1798

Port Orchard, Washington

©1999-2006 Leader International Corporation,  
FairWeather Site Furnishings division