



SPECIFICATIONS

MATERIAL

The EA-1T-L bollard shall be fabricated with 3 extruded aluminum panels with distinctive grooves (Average wall thickness .10). The panels interlock to form the bollard. Each 30" light column shall have a 3" spacer at the top and one at the bottom. EA-1T-L bollard shall have a 1/2" x 6 3/4" triangular aluminum top and 5/8" x 9" triangular aluminum base with 1/2" holes for anchor bolts. **Anchor bolts by others.**

LIGHTS

3 each 30 inch Plexineon® LED bright white lights, 6500 Kelvin. Electrical input: standard 120v line, input range 100 Vac – 240 Vac/0.3A, low voltage 24 volt/20 watt transformer. Complies with UL 2108, CSA C22.2 No. 250, Listing #E112419.

Plexineon is protected under U.S. Pat. No. 6,592,238 and "iLight" and "Plexineon" are Registered Trademarks of iLight Technologies, Inc., Evanston, Illinois

HARDWARE

Bollard top shall be attached with 3 stainless steel tamper resistant bolts.

PROTECTIVE COATINGS

Anodized finish **or** powder coating

Anodized finishes: Clear or Bronze anodized coating.

Anodizing meets the following standards:

MIL-A-8625 Type 2, AMS 2471, 2472 and
ASTM-B-580 types B, C, D, E, F

Powder Coating: Following fabrication bollards shall be cleaned and treated with an iron phosphate process. Following pretreatment, the lighted bollards are coated with a polyester or polyester TGIC topcoat on the outside of the bollard. The coating shall be a minimum of 4 mils thick on all surfaces.

Options:

Mounting: Surface mount or cast in place

Lighting: Available in any combination of eight Plexineon® colors

Heights: 36" and 24" standard

Model EA-1T-L 36" LED Lighted Bollard

FairWeather Site Furnishings

360-895-2626 or Toll Free 800-323-1798

Port Orchard, Washington

©2005-2007 Leader International Corporation,
FairWeather Site Furnishings division