



NOTE: BOLT DOWN HOLE LOCATIONS 1" LESS THAN OUT TO OUT DIMENSIONS

SPECIFICATIONS

MATERIAL

The PL-3 bench is constructed of mild steel in three sections consisting of two end sections and one seat section. All parts are drilled and precisely formed for quick assembly. End sections are made with 1" x 1" solid steel bar stock. All seat sections shall be fabricated with 1" sch. 40 pipe and 1/4 x 1-1/2" mild steel strap. Steel shall conform to ASTM A36 hot rolled steel. All steel shall be wheelabrated prior to fabrication.

HARDWARE

Fasteners shall be 3/8 socket head cap screws with vandal resistant pins.

Anchor bolts by others

PROTECTIVE COATINGS

Powder Coating: All Metal, Following fabrication shall be cleaned and treated with an iron phosphate process prior to the coating application. This process shall include a non-chromated alkaline cleaner and an iron phosphate treatment followed with an acidic sealer for maximum adhesion. The protective coatings shall be either polyester or polyester TGIC powder. Following application the parts shall be baked until properly cured. The coating shall be a minimum of 4 mils thick on all surfaces.

OPTIONS

Length: 4, 5, 6, 8 ft. standard, other lengths available

PL-3 bench lengths up to 8 ft available without an additional frame. All benches longer than 8ft. will require a center frame.

Plaza Series, Model PL-3 Bench

FairWeather Site Furnishings

360-895-2626 or Toll Free 800-323-1798

Port Orchard, Washington

©1999-2003 Leader International Corporation,
FairWeather Site Furnishings division