



SPECIFICATIONS

MATERIAL

The B-1, 8" Post-Top Beacon shall be fabricated with 8" .188 wall pipe (8.625" OD), welded to 2 ea. 1 1/2 inch wide decorative collars (9.625" OD) and a schedule 40 weld cap. Steel shall conform to ASTM A53.

Mounting plate shall be 1/8" SS recessed inside base collar and have (4) 1/2" mounting holes for anchor bolts. Anchor bolts by others.

LIGHTS

3 ea. 4 inch and 3 ea. 6 inch Plexineon® LED bright white lights, 6500 Kelvin. Electrical input: standard 120v line, input range 100 Vac – 240 Vac/0.3A, low voltage 24 volt/20 watt transformer. Complies with UL 2108, CSA C22.2 No. 250, Listing #E112419.

Plexineon is protected under U.S. Pat. No. 6,592,238 and "Light" and "Plexineon" are Registered Trademarks of iLight Technologies, Inc., Evanston, Illinois

HARDWARE

Bollard top shall be attached to base with 3 stainless steel tamper resistant bolts.

PROTECTIVE COATING

Powder Coating: Following fabrication bollards shall be cleaned and treated with a 7 stage iron phosphate process. Following pretreatment, the lighted bollards are coated inside and out with a corrosion resistant epoxy powder primer followed by a polyester or polyester TGIC topcoat on the outside of the bollard. The coating shall be a minimum of 4 mils thick on all surfaces.

Note: Unless otherwise specified, bollards shall be powder coated a standard FairWeather color.

Options: Available in any combination of eight Plexineon® colors

Model B-1, 8" LED Post-Top Beacon

FairWeather Site Furnishings

360-895-2626 or Toll Free 800-323-1798

Port Orchard, Washington

©1999-2006 Leader International Corporation,
FairWeather Site Furnishings division