



SPECIFICATIONS

MATERIAL

The PTR-8 Planter shall be fabricated with 1/2" steel rod welded to 1/4" x 2" horizontal steel hoops. All steel shall conform to ASTM A36 hot rolled steel and shall be wheelabrated prior to fabrication.

Optional wall lining shall be formed from 20 gauge steel powdercoated to match. (Note: these do not have bottoms.)

WELDS

All welds shall be smooth, continuous fillet welds ground smooth where necessary to remove any burrs or sharp edges.

PROTECTIVE COATINGS

Powder Coating: Following fabrication metal elements shall be cleaned and treated with an iron phosphate process prior to the coating application. This process shall include a non-chromated alkaline cleaner, and an iron phosphate treatment followed with an acidic sealer for maximum adhesion. The protective coatings shall be either polyester or polyester TGIC powder. Following application the parts shall be baked until properly cured. The coating shall be a minimum of 4 mils thick on all surfaces.

Anchor bolts by others.

OPTIONS

Other heights available
wall lining

Note:

Insert for potting soil provided by others.

REV 8-10-06

PTR-8 Planter

FairWeather Site Furnishings

360-895-2626 or Toll Free 800-323-1798
Port Orchard, Washington

©1999-2006 Leader International Corporation,
FairWeather Site Furnishings division